



STACKER CARS RULES

General Safety Rules

1. A basic 4-point cage is highly recommended.
2. All side glass must be removed or rolled down 100%. Windshield or rear windows are optional.
3. A steel door plate (highly recommended) may be welded or bolted over the driver's side door.
4. All doors must be welded or chained shut.
5. Having a horizontal crush bar from side to side just behind the driver's seat is recommended.
6. Having a vertical crush/rollover bar behind the driver's seat is recommended.
7. If a battery is in the back seat, it must be securely covered and tightly strapped down.

General Construction Guidelines of Bottom Car

1. The bottom car is responsible for gas and braking.
2. Cars must be stock.
3. Front wheel drive compact cars and/or Mid-Size FWD cars
4. NO RACE CARS WILL BE ALLOWED FOR THE BOTTOM CAR.
5. Stock suspension, stock engine and stock transmission. The theme here is STOCK.
6. The bottom car will have no steering components whatsoever.
7. Windshield or safety bars must remain in the vehicles.
8. 7" wide maximum stock or safety wheels. No more than a 3.5" backset on any wheel.

Page 3

9. Stock DOT radial tires (i.e. any 55, 60, 65, 70, 75 or 80 series radial tire 165-215). No trick, racing or exotic tires. No Z-rated tires. No wheel spacers of any kind. lift or bobcat tires.

General Construction Guidelines for the Top Car

1. The top car will do all steering.
2. The complete body shell from bumper to bumper must remain intact, including the front and rear firewalls.
3. All suspension, engine, K-frame, wheels and tires may be removed.
4. The complete body including the front and rear tail panels, bumpers and the full body between the bumpers is required so the car body up top resembles that of a full car.

The number of laps run will depend on car count.

No 2-way radios or other communication devices are allowed.